

**Products with volatile solvent - film: solid, transparent**

## **FAMCORTIL<sup>®</sup> 400**

**FAMCORTIL<sup>®</sup> 400 is protective anticorrosion coating made of carefully selected corrosion inhibitors, microwaxes, components for penetration and adhesion increase and easily volatile organic solvent.**

### **ADVANTAGES**

- Non-sticky, transparent, dry, elastic film remains on protected surfaces after solvent evaporation
- It provides protection to treated surfaces up to 3 years in conditions of indoor storage, i.e. up to 18 months in outdoor area.

### **QUALITY LEVEL**

ISO-L-RF

MIL-C-16173 D/IV

### **APPLICATION**

**FAMCORTIL<sup>®</sup> 400** is intended for outdoor and indoor protection, for continental or overseas transportation. It is used for anticorrosion protection of outdoor machined and non-machined surfaces, tool and other machines, plants, spare parts, semi-finished products, finished products and external engine surfaces.

**FAMCORTIL<sup>®</sup> 400** is applied by coating, immersion or spraying, at room temperature on clean, degreased and dry surfaces. In case of spraying application, operating pressure is 6-9 bars. Applied film is completely dry after 4 to 6 hours.

### **TYPICAL CHARACTERISTICS**

CHARACTERISTICS	UNITS	<b>FAMCORTIL<sup>®</sup> 400</b>	METHODS
Flash point	°C	Min.38	SRPS EN ISO 2719
Anticorrosion protection wet chamber	h	Min.336	ASTM D 1748
Protective film thickness	µm	Min. 40	MIL C 16173 D
Nen-evaporable material content	%	Min.45	MIL C 16173 D t 4.6.2
Coverage	m <sup>2</sup> /l	10-15	-

### **NOTES FOR SAFETY AT WORK**

- Do not apply the product to the heated surfaces and near the open flame,
- When applying, take measures to protect the respiratory tract, eyes and hands



#### STORAGE

Store in a confined space, intended for the storage of flammable materials. Tightly closed original containers should not be stored in places exposed to direct sunlight, nor at temperatures below 5°C. All necessary instructions can be found in the Safety Data Sheet. It contains details of possible hazards, warnings and first aid measures, as well as the environmental impact and the necessary measures when storing.

#### PACKING

Tin pails of 17 kg and tin drums of 180 kg.

---

**Data are orientational, manufacturer reserves the right to make changes in order to improve product quality.**



December, 2016

FABRIKA MAZIVA FAM • Jug Bogdanova 42 • 37000 Kruševac • Serbia  
Tel. ++381 37 422078; 423261 • Fax. ++ 381 37 426241; 424008  
[www.fam.rs](http://www.fam.rs)