

Anticorrosion oil

FAMCORTIL[®] SK FAMCORTIL[®] SK-L

FAMCORTIL[®] SK and FAMCORTIL[®] SK-L is anticorrosion oil with good lubricating properties.

ADVANTAGES

- On protected surfaces remains adhesive, oily, non-drying protective film enabling good mobility of the assembly block in all climate conditions
- Oil viscosity is adjusted according to application season, therefore it is produced in two variants:

FAMCORTIL SK for the application in winter conditions

FAMCORTIL SK-L for the application in summer period

QUALITY LEVEL

ISO-L-AY

APPLICATION

FAMCORTIL[®] SK and FAMCORTIL[®] SK-L is intended for the lubrication of mechanisms of rough making of railway vehicle axles, railway switches in medium and severe climate conditions.

FAMCORTIL[®] SK and FAMCORTIL[®] SK-L is applied to the application point by coating, spraying procedures, etc.

TYPICAL CHARACTERISTICS

CHARACTERISTICS	UNITS	FAMCORTIL[®] SK	FAMCORTIL[®] SK-L	METHODS
Density at 15°C	g/ml	Typ.0.892	Typ.0.899	SRPS EN ISO 3675
Flash point	°C	Min.180	Min.200	SRPS EN ISO 2592
Kinematic viscosity at 40°C	mm ² /s	Min.39	Min.75	SRPS ISO 3104
Pour point	°C	Max.-35	Max.-25	SRPS ISO 3016

STORAGE

Store in a confined space. Do not store at elevated temperatures, nor in places exposed to direct sunlight, nor at temperatures below 5°C. All necessary instructions can be found in the Safety Data Sheet. It contains details of possible hazards, warnings and first aid measures, as well as the environmental impact and the necessary measures when storing.

PACKING

Plastic canisters of 20 kg and tin drums of 180 kg.

Data are orientational, manufacturer reserves the right to make changes in order to improve product quality.

December, 2016



December, 2016

FABRIKA MAZIVA FAM • Jug Bogdanova 42 • 37000 Kruševac • Serbia
Tel. ++381 37 422078; 423261 • Fax. ++ 381 37 426241; 424008
www.fam.rs