

**Engine oil for two-stroke engines**  
**ISO L-EGD**

# FAMDUOTAKT<sup>®</sup> SINT

FAMDUOTAKT<sup>®</sup> SINT is fully synthetic oil for new generation two-stroke gasoline engines which use mixture of oils with high octane gasoline (super 98 and unleaded gasoline BMB 95).

## ADVANTAGES

- Excellent lubricity properties;
- Excellent miscibility with fuel;
- Excellent mixture combustion;
- Extraordinary engine protection against formation of deposits and soot;
- Reduced exhaust emission.

## QUALITY LEVEL

ISO 6743-15

ISO L – EGD

API TC<sup>+</sup>

JASO FD

PIAGGIO HEXAGON

STIHL

HUSQUARNA 272/254

IT MEETS THE TESTS:

YAMAHA RD350B

YAMAHA CE50S

KAWASAKI KH125M

## APPLICATION

FAMDUOTAKT<sup>®</sup> SINT is synthetic engine oil intended for the lubrication of modern two-stroke gasoline engines of motorcycles, chainsaws Husquarna, Stihl Partner, Dolmar ....., motor-cultivators, mowers, water pumps, outboard motors etc, which are fueled by the mixture of oil with high octane gasolines.

FAMDUOTAKT<sup>®</sup> SINT extremely well lubricates and protects the engine against wear at maximum load. It also prevents the creation of coke deposits and soot in the engine, thus preventing the effect of self-ignition of the mixture.

FAMDUOTAKT<sup>®</sup> SINT can be mixed with the fuel according to the engine manufacturer recommendations and the most frequently required mixture is of 2-3%

## TYPICAL CHARACTERISTICS

	TYPICAL VALUE	METHOD
Appearance	clear red liquid	visual
Density at 15°C, g/ml	0,88	SRPS EN ISO 3675
Kinematic viscosity at 40°C, mm <sup>2</sup> /s	82	SRPS ISO 3104
Flash point, °C	95	SRPS EN ISO 2592
Pour point, °C	-36	SRPS ISO 3016
Cu corrosion, 3h/121°C, degree	1	SRPS EN ISO 2160

December, 2016

FABRIKA MAZIVA FAM • Jug Bogdanova 42 • 37000 Kruševac • Serbia

Tel. ++381 37 422078; 423261 • Fax. ++ 381 37 426241; 424008

www.fam.rs



#### STORAGE

Store in covered area. If stored outdoors, it is necessary to place the drums in a horizontal position to prevent the accumulation of water on the surface of the drum. Do not store at elevated temperatures or in locations exposed to direct sunlight.

All necessary instructions can be found in the product SDS. It contains the details of possible hazards, warnings and first aid measures, as well as the impact on the environment and the necessary measures for the storage and handling.

#### PACKING

Drums 180 kg, plastic cans of 0,1L, 0,25L and 0,5L.

---

Data are orientational, manufacturer reserves the right to make changes in order to improve product quality.



December, 2016

FABRIKA MAZIVA FAM • Jug Bogdanova 42 • 37000 Kruševac • Serbia

Tel. ++381 37 422078; 423261 • Fax. ++ 381 37 426241; 424008

[www.fam.rs](http://www.fam.rs)