

Oil for tractor engine, transmission and hydraulics ISO L-E/C/H

FENIX[®] SUPER TRAKTOL

FENIX[®] SUPER TRAKTOL is high quality multipurpose tractor oil STOU (Super Tractor Oil Universal), specially formulated and developed for efficient lubrication of mechanical parts, clutches, including those with sophisticated design on tractors with modern design.

ADVANTAGES

- Engine oil with high detergent and dispersing properties and good thermal and oxidation stability, good antiwear and anticorrosion protection;
- Transmission oil with capability of enduring high pressures, also suitable for the lubrication of hypoid gears;
- Hydraulic oil that meets the requirements of hydraulic systems in high and low temperatures;
- It is used for the lubrication of wet brakes and gears thus providing safe braking and good operation of reducer components.

QUALITY LEVEL

| | |
|--------------------|---------------------------------------|
| API CF-4/CE/SF | Massey Ferguson CMS M1139/M1144/M1145 |
| ACEA E2 | FORD M2C 159B |
| MB 227.1/ 228.1 | API GL-4 |
| MIL-L-2104D | Allison C-4 |
| John Deere JDM J27 | ZF TE-ML 06B, 06D, 07B |
| | Caterpillar TO-2 |

APPLICATION

FENIX[®] SUPER TRAKTOL is high quality universal oil meeting requirements for the lubrication of diesel engines with and without turbocharging, gearboxes, transmissions, differentials and gears, hydraulic systems and wet brakes of tractors.

FENIX[®] SUPER TRAKTOL can be used as engine oil for transportation vehicles and other equipment thus limiting exclusively to its characteristics of being multifunctional oil.

TYPICAL CHARACTERISTICS

| | TYPICAL VALUE | METHOD |
|--|---------------|------------------|
| Density at 15°C, g/ml | 0,88 | SRPS EN ISO 3675 |
| Kinematic viscosity at 40°C, mm ² /s | 81 | SRPS ISO 3104 |
| Kinematic viscosity at 100°C, mm ² /s | 11 | SRPS ISO 3104 |
| Viscosity index | 135 | SRPS ISO 2909 |
| Flash point, °C | 220 | SRPS EN ISO 2592 |
| Pour point, °C | -33 | SRPS ISO 3016 |
| Cu corrosion, 3h/150°C, degree | 1 | SRPS EN ISO 2160 |



STORAGE

Store in covered area. If stored outdoors, it is necessary to place the drums in a horizontal position to prevent the accumulation of water on the surface of the drum. Do not store at elevated temperatures or in locations exposed to direct sunlight.

All necessary instructions can be found in the product SDS. It contains the details of possible hazards, warnings and first aid measures, as well as the impact on the environment and the necessary measures for the storage and handling.

PACKING

Drums 180kg and containers of 10L and 5L.

Data are orientational, manufacturer reserves the right to make changes in order to improve product quality.



December, 2016

FABRIKA MAZIVA FAM • Jug Bogdanova 42 • 37000 Kruševac • Serbia

Tel. ++381 37 422078; 423261 • Fax. ++ 381 37 426241; 424008

www.fam.rs