

Engine oils

ISO L-E

FENIX[®] UNIVERZAL S SAE 15W-40

FENIX[®] UNIVERZAL S SAE 15W-40 is highly efficient multigrade engine oil made from specially selected additives and high quality solvent neutral base oils for the lubrication of four-stroke gasoline and diesel engines of older generation in all operating conditions.

ADVANTAGES

- High alkaline reserve level;
- Excellent shear stability;
- Good thermal and oxidation stability;
- Improved protection against wear and corrosion of engine parts;
- Easy engine start and application at all seasons;
- Improved cold start compared to monograde engine oils.

QUALITY LEVEL

ISO 6743-15
API CF/CD/SF
MIL-L-2104D
MB 227.1

APPLICATION

FENIX[®] UNIVERZAL S SAE 15W-40 is used for the lubrication of four-stroke gasoline engines and diesel engines of commercial vehicles, engines of construction and agricultural machinery as well as stationary drive units that work with variable load in moderate and severe conditions of exploitation.

TYPICAL CHARACTERISTICS

	TYPICAL VALUE	METHOD
Density at 15°C, g/ml	0,88	SRPS EN ISO 3675
Kinematic viscosity at 40°C, mm ² /s	94	SRPS ISO 3104
Kinematic viscosity at 100°C, mm ² /s	13	SRPS ISO 3104
Dynamic viscosity at -20°C, mPas	6900	DIN 53018/1
Viscosity index	130	SRPS ISO 2909
Flash point, °C	230	SRPS EN ISO 2592
Pour point, °C	-30	SRPS ISO 3016
TBN, mg KOH/g	9	SRPS ISO 3771
Sulphated ash, %	1,2	SRPS ISO 3987



STORAGE

Store in covered area. If stored outdoors, it is necessary to place the drums in a horizontal position to prevent the accumulation of water on the surface of the drum. Do not store at elevated temperatures or in locations exposed to direct sunlight.

All necessary instructions can be found in the product SDS. It contains the details of possible hazards, warnings and first aid measures, as well as the impact on the environment and the necessary measures for the storage and handling.

PACKING

Drums 175kg, plastic containers of 1L, 4L and 10L.

Data are orientational, manufacturer reserves the right to make changes in order to improve product quality.



December, 2016

FABRIKA MAZIVA FAM • Jug Bogdanova 42 • 37000 Kruševac • Serbia

Tel. ++381 37 422078; 423261 • Fax. ++ 381 37 426241; 424008

www.fam.rs