

## Oils for tractor hydraulics and transmission ISO L-C/H

# TRANSHIDO T

TRANSHIDO T is multipurpose tractor oil (UTTO), multigrade SAE 10W-30, manufactured from solvent neutral base oils and additives. Extremely good antiwear, antifoaming and anticorrosion properties as well as good thermal-oxidation stability of this oil provide reliable system and long-lasting operation of hydraulic transmission system and wet brakes of tractors in all weather conditions.

### ADVANTAGES

- Excellent antiwear protection ensures a long lifetime of the gears;
- Low friction coefficient ensures that wet brakes and clutch operate quietly and without vibrations;
- High thermal and oxidation stability prevents the formation of deposits and sludge;
- Good anticorrosion protection protects parts even in the presence of moisture;
- Compatibility with sealing elements.

### QUALITY LEVEL

API GL-4	GM Allison C-4
John Deere JDM J 20C/J 20D	ZF 03E/05F/06K/17E
MF CMS M1135/ M1141/ M1143/ M1145	AGCO 821-XL
CNH MAT 3505/3506/3509/3525/3526/3510	AGCO Q-186
Ford M2C 134-D	Komatsu
Ford M2C 86-B/C	Landini

### APPLICATION

TRANSHIDO T is universal transmission tractor oil (UTTO) used for hydraulics, transmissions and wet tractor brakes. This oil can be used as a hydraulic-transmission oil for agricultural and construction machinery, for gearboxes, differentials, drive shafts, power transmissions for the operation of connecting machines, for planetary reducers, etc.

### TYPICAL CHARACTERISTICS

	TYPICAL VALUE	METHOD
Density at 15°C, g/ml	0,87	SRPS EN ISO 3675
Kinematic viscosity at 40°C, mm <sup>2</sup> /s	80	SRPS ISO 3104
Kinematic viscosity at 100°C, mm <sup>2</sup> /s	11	SRPS ISO 3104
Viscosity index	130	SRPS ISO 2909
Flash point, °C	225	SRPS EN ISO 2592
Pour point, °C	-33	SRPS ISO 3016
Cu corrosion, 3h/121°C, degree	1	SRPS EN ISO 2160



#### STORAGE

Store in covered area. If stored outdoors, it is necessary to place the drums in a horizontal position to prevent the accumulation of water on the surface of the drum. Do not store at elevated temperatures or in locations exposed to direct sunlight.

All necessary instructions can be found in the product SDS. It contains the details of possible hazards, warnings and first aid measures, as well as the impact on the environment and the necessary measures for the storage and handling.

#### PACKING

Drums 180kg, 60L and plastic containers of 20L, 10L and 5L.

---

Data are orientational, manufacturer reserves the right to make changes in order to improve product quality.



December, 2016

FABRIKA MAZIVA FAM • Jug Bogdanova 42 • 37000 Kruševac • Serbia

Tel. ++381 37 422078; 423261 • Fax. ++ 381 37 426241; 424008

[www.fam.rs](http://www.fam.rs)